

DOUBLE NET COCONUT - DC 2

GreenSolutions™ Coconut Erosion Control Blankets consist of 100% mattress grade coconut fiber mechanically bound and covered on both sides by netting. The coconut fiber is homogeneously blended and evenly distributed throughout the blanket. The netting is UV stabilized polypropylene with mesh openings of approximately 5/8 in. by 5/8 in. The blanket is sewn on approximately 2 in centers with photodegradable polypropylene thread.

PROPERTY	TEST METHOD	ENGLISH	METRIC
Roll Size		8 ft X 112.5 ft	2.4 m x 34.29 m
Roll Weight		55 lbs +/-	25 Kg
Physical			
Mass / Unit Area	ASTM D 6475	8.82 oz / yd ²	298 g / m ²
Thickness	ASTM D 6525	0.30 in	7.6 mm
Mechanical			
Grab Tensile Strength	ASTM D 6818	150 x 150 lb / ft	2.2 x 2.2 kN / m
Grab Elongation	ASTM D 6818	25%	25%
Endurance			
Functional Longevity	Observed	Up to 36 months	Up to 36 months

- All values are minimum average roll values unless otherwise stated.
- Longevity may vary depending on the area in which the product is installed.

Manufactured by: Industrial Fabrics – 510 O’ Neal Lane – Baton Rouge, LA 70819
 225-273 9600 Phone – 225-273 0440 Fax
www.greensolutions.us

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT FURNISHED HEREUNDER OTHER THAN AT THE TIME OF DELIVERY IT SHALL BE OF THE QUALITY AND SPECIFICATION STATED HEREIN. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED, AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE, ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. ANY RECOMMENDATIONS MADE BY SELLER CONCERNING THE USES OR APPLICATIONS OF SAID PRODUCT ARE BELIEVED RELIABLE AND SELLER MAKES NO WARRANTY OF RESULTS TO BE OBTAINED. IF THE PRODUCT DOES NOT MEET IFI CURRENT PUBLISHED SPECIFICATIONS AND THE CUSTOMER GIVES NOTICE TO IFI BEFORE INSTALLING THE PRODUCT, THEN IFI INC. WILL REPLACE THE PRODUCT WITHOUT CHARGE OR REFUND THE PURCHASE PRICE.