

TURF REINFORCEMENT MAT (TRM) - GS 50

GreenSolutions™ GS 50 TRM is a machine stitched Heavy-Duty Polypropylene Turf Reinforcement Mat utilized for protection of shorelines, channels, and extreme slopes. GS 50 is comprised of an evenly distributed matrix of U.V. stabilized polypropylene/synthetic fibers that are stitch-bonded between two layers of biaxially oriented Heavy-Duty polypropylene netting. The fiber and netting components are stitched on 1.5" centers using a polypropylene thread. All components used to manufacture GS 50 are non-biodegradable and are resistant to U.V. and chemical degradation.

GS 50 is designed to achieve a functional longevity greater than 3 years, in order for to provide for sufficient vegetation establishment. GS 50 offers both long-term and immediate protection to shorelines, channels, and extreme slopes. The open area of GS 50 allows for soil filling and further seed germination, which in time creates a matrix of soil, roots, and vegetation that will protect your project for years to come.

PROPERTY	TEST METHOD	ENGLISH	METRIC
*Roll Size		8 ft X 112.5 ft	2.4 m x 34.29 m
Physical			
Mass / Unit Area	ASTM D 6566	10.0 oz / yd ²	340 g / m ²
Thickness	ASTM D 6525	0.40 in	10.1 mm
Light Penetration (% Passing)	ASTM D 6567	20%	20%
Color	Visual	Green	
Mechanical			
Grab Tensile Strength	ASTM D 6818	400 x 300 lb / ft	5.8 x 4.3 kN / m
Grab Elongation	ASTM D 6818	50% (max)	50% (max)
Resiliency	ASTM D 6524	90%	90%
Flexibility	ASTM D 6575	0.026 in / lb (avg)	30,000 mg / cm (avg)
Endurance			
UV Resistance @ 1000 hours	ASTM D 4355	80%	80%
Performance			
Velocity ³ (Vegetated)	Large Scale	17 ft / s	5.2 m / s
Shear Stress ³ (Vegetated)	Large Scale	10 lb / ft ²	479 Pa
Manning's "n" ⁴ (Unvegetated)	Calculated	0.025	0.025
Seedling Emergence	ECTC Draft Method #4	409%	409%

- All values are minimum average roll values unless otherwise stated.
- Longevity may vary depending on the area in which the product is installed.

Your Erosion Control Solutions Provider

**NATIONAL
MANUFACTURER
& SUPPLIER**

*** Available in 16 ft and Master Rolls**

Manufactured by: **Industrial Fabrics** – 510 O' Neal Lane – Baton Rouge, LA 70819
 225 273 9600 | 800 848 4500
www.greensolutions.us

EXCLUSIVE LIMITED WARRANTY

LIMITED WARRANTIES. Seller, Industrial Fabrics, Inc., warrants that its products ("Products") sold are substantially free from defects in material and workmanship at the time of delivery. There are no express or implied warranties with respect to Products or their condition related to the transportation, installation, performance, maintenance, or actual use of the Products. SELLER MAKES NO OTHER WARRANTY WHATSOEVER, EXPRESS OR IMPLIED. ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND ALL IMPLIED WARRANTIES OF FITNESS FOR ANY PARTICULAR PURPOSE ARE DISCLAIMED BY SELLER AND ARE NOT PART OF THE SALE. SELLER DOES NOT WARRANT ANY USES OR RESULTS OF THE USE OF THE PRODUCTS.

LIMITATION OF REMEDIES AND LIABILITY. Regarding the Products and any alleged damages arising out of or related to the use or purchase of the Products, Seller's liability shall be limited to replacement of Products that are defective in material or workmanship at the time of delivery. The supply of the replacement product is the sole remedy of the buyer for any alleged defective Products purchased from Seller by the buyer. Seller's liability specifically excludes the cost of removal and/or installation of the Products. Seller's total liability in any way arising from or relating to the Products shall not exceed the purchase price paid by Buyer for such Products. Buyer's sole and exclusive remedies are limited to those provided in this paragraph. SELLER SHALL HAVE NO LIABILITY TO BUYER OR BUYER'S CLIENTS FOR LOST INCOME, CONSEQUENTIAL, SPECIAL, PUNITIVE OR INCIDENTAL DAMAGES OF ANY TYPE, REGARDLESS OF WHETHER THE CLAIMS ARISE IN CONTRACT, WARRANTY, STRICT LIABILITY OR NEGLIGENCE.